

EXTENDERS (TX+RX)	Video Support							Key Features										Max Distance*				Related Products					
	HDMI	HDCP	Full 1080p HD	4K @60Hz 4:2:0 8 Bit	4K @60Hz 4:4:4 8 Bit	4K HDR	Max Bandwidth (Gbps)	Power	ARC	HDMI Loop Out	Optical Audio Return	SPDIF	Audio De-em-bedding	Bi-directional USB	Dual Ethernet Passthrough	Ethernet	RS-232	Bi-directional IR	4K over Cat5e/6	4K over Cat6a/7	1080p over Cat5e/6	1080p over Cat6a/7	Extender Pair with IR Kit	Extender Pair with Wall Plate Rx	Receiver ONLY	Transmitter ONLY	
4K Ultra HD (Fiber)																											
B10-FBR-EXT-18G (Fiber)	2.0+	2.2	√	√	√	√	18.0		√									√	1000 (fiber)	1000 (fiber)	1000 (fiber)	1000 (fiber)					
B-760-EXT-444-300 (Fiber)	2.0+	2.2	√	√	√	√	18.0										√	√	1000 (fiber)	1000 (fiber)	1000 (fiber)	1000 (fiber)					
4K Ultra HD (HDBaseT)																											
B-660-EXT-444-40	2.0+	2.2	√	√	√	√	18.0	POC	√		√					√	√	√	115	130	200	230					
B-600-EXT-330-RS-IP	2.0+	2.2	√	√			10.2	POE	√		√		√			√	√	√	300	330	330	330					
B-560-EXT-444-70	2.0+	2.2	√	√	√	√	18.0	POC						√		√	√	√	230	330	330	330					
B-540-EXT-330-RS-IP	2.0+	2.2	√	√			10.2	POC								√	√	√	230	330	330	330	KIT-540-330-SM-IRF	B-540-EXT-330-RS-IPW			
B-540-EXT-230-RS	2.0+	2.2	√	√			10.2	POC									√	√	115	130	200	230	KIT-540-230-SM-IRF				
KIT-540-TX-RX-330-IR	2.0+	2.2	√	√			10.2										√		230	330	330	330			B-540-RX-330-IR	B-540-TX-330-IR	
B-540-EXT-230-IR	2.0+	2.2	√	√			10.2	POC										√	115	130	200	230					
B-360-1CAT-30	2.0+	2.2	√	√	√		18.0	POC										IR Passthrough for RX to TX		98	164	164					
Full 1080p HD (HDBaseT)																											
B-520-EXT-330-RS-IP	1.4	1.4	√				10.2	POC								√	√	√			330	330	KIT-520-330-SM-IRF	B-520-EXT-330-RS-IPW			
KIT-520-TX-RX-230-IR	1.4	1.4	√				10.2											√			230	230			B-520-RX-230-IR	B-520-TX-230-IR	
B-520-EXT-230-RS	1.4	1.4	√				10.2	POC									√	√			230	230	KIT-520-230-SM-IRF	B-520-EXT-230-RS-W			
B-520-EXT-330-HV	1.4	1.4	√				10.2	POC								√	√	√			330	330					
Full 1080p HD (Other)																											
B-700-EXT-1K-RS (Fiber)	1.4	1.4	√				6.75										√	√			1000	1000					
B-330-1CAT-40	1.3b	1.4	√				6.75											IR Passthrough for RX to TX			130	130					
B-320-1CAT-HDIR (1CAT)	1.4	1.4	√				6.75											√			130	130	KIT-320-1CAT-SM-IRF	B-320-1CAT-HDIR-W			
B-400-1COAX-HDIR (1COAX)	1.4	1.4	√				6.75											√			400	400					
HD-2CAT-1080P-130 (2CAT)	1.4	1.4	√				6.75											√			130	130					
B-200-5COAX-HDIR	1.4	1.4	√				6.75											√			250	250					